

Code of Practice for the Design, Installation and Seismic Restraint of Suspended Ceilings

Project Team – Ruth Berry, BRANZ Keith Hogg, Hush Interiors John Keen, USG Boral John Parkin, AWCINZ Dennis Prout, Forman Building Systems











- Despite requirements of various NZ Standards, the seismic compliance of ceilings has received scant attention in recent years
- Canterbury and the more recent Wellington and Seddon earthquakes have highlighted a systematic problem



Canterbury University Report

- Review of Design & Installation Practices for Non-Structural Components
- Ceilings, facades & partitions
- Three workshops held at Canterbury University in 2011
- A range of technical & regulatory recommendations
- Restraints of ceilings & other NSE mandatory under Building Code




- Well over half the cost incurred in the Christchurch earthquakes were associated with non structural elements such as ceilings, partitions and services.
- The cost of non structural element failures had resulted in otherwise repairable buildings being demolished.
- Buildings completed post earthquake often are noncompliant

AWCI



AWCI










AWCI









AWCI Industry Forums

- Held in 2012
- Lack of restraint detail on tender documents
- No integrated design provided of in-ceiling services
- Tenderers are not provided with necessary information or have the resources to design restraint systems
- Ceiling contractors are not Seismic Engineers
- AS / NZS 2785:2000 Suspended Ceilings Design & Installation long overdue in need of review



AWCI / BRANZ Partnership

to develop an industry Code of Practice



<u>Objectives</u>

- To create greater awareness in the construction sector from design to sign-off, of requirements and conditions for suspended ceilings that are appropriately designed and installed to meet appropriate seismic performance limits in compliance with the NZBC
- Reduced earthquake damage (and associated cost repair) caused by suspended ceiling failure
- To become a cited document in the Building Code as an acceptable solution





• Designers, engineers, project managers, suppliers, installers and building officials for seismic design, installation & certification of suspended ceilings



The adoption of this Code of Practice will lead to

- Reduced damage
- Reduced repair cost
- Reduced length of time to re-occupy post event



Code of Practice Contents

Background Introduction **Design Documentation** Design Suspended Ceiling Types Fire & Suspended Ceilings Acoustics Possible Reasons & **Consequences of Failure** Tendering Installation **Roles & Responsibilities** Monitoring Design & Construction Appendices Maintenance




<u>Design</u>

Integrated design at the earliest possible stage leads to

- More accurate costings
- Better & faster installation
- Fewer variations
- Fewer time delays
- Fewer site conflicts
- Compliance



Seismic Grade



High

Extent of seismic restraints, engineering, design, monitoring & certification



Identifying the Seismic Grade of each ceiling

- Structural Engineer to make conservative assumptions on
 - Site subsoil category
 - Building & ceiling risk category
 - Building & ceiling ductility
 - Period of vibration



Design Documentation

<u>What Engineers need!!!</u> What Contractors need !!!

- All the necessary information to calculate a compliant design
- All the necessary information to calculate and/or cost a compliant design



Information needed with consent and required in specification

- Building Classification
- Importance level
- Category
- ULS or SLS
- Return periods
- PS1 PS4 ??

Why?

- So it can be done right
- Or else assumptions will rule
- PS 3's only lead to abuse



Possible reasons for failure

of suspended ceilings

- Unsuitable ceiling design
- The use of an unsuitable product / system
- Installation not meeting manufacturer, supplier or NZ Building Code requirements
- Ceiling wires not installed correctly
- Services in the ceiling space or connected to the ceiling grid not installed to the current Standards / Building Code requirements



- Perimeter walls or bulkheads insufficient to receive line loads of the ceiling
- Insufficient seismic gaps to allow for movement of the building structure
- Partitions being connected to the ceiling system but not independently braced
- A lighter gauge of ceiling grid or non-tested system being installed outside of its non structural capacity



 Interference from non – structural building components in the plenum



<u>Tender</u>

- Usually no restraint detail on tender documents
- Four common tendering scenarios
 - Seismic restraints are tagged out
 - Provisional Sums nominated
 - Seismic Engineer employed to design restraints
 - Restraints are ignored

Guess which tender wins????

AWCI AWCI Tendering Protocol for

Association of WALL & CEILING INDUSTRIES of New Zealand, Inc.

Grid Suspended Ceiling Installations

 Simulat appets any example to such while the SIMCE TRADES of the such explores of SIMCE -TRADES. SiMCE means are example to such while the pit appets offsp basis on the SIMCE Techniq Provides are example. Option for said phases even to 66 Support Charge hole: Option for said phases even to 66 Support Charge hole: Option for said phases even to 66 Support Charge hole: Option for said phases even to 66 Support Charge hole: Option for said phases even to 66 Support Charge hole: Option for said phases even to 66 Support Charge hole: Option for said phases even to 66 Support Charge hole: Option for said phases even to 66 Support Charge hole: Option for said phases even to 66 Support Charge hole: Option for said phases even and the Support Charge phase hole: Option for said phases even and the Support Charge phase hole: Option for said phases even and the Support Support Phase Phase hole: Option for said phase hole: Massa and said phase even and the Support for SUP results of the Support Phase Phase hole: Option for said phase hole:<th>nin 10 10 10 10</th>	nin 10 10 10 10
 Follations reaction calculation provide the statistic product accounter and and or document. This gots is private a second with producting and uraged water, and to save this conflict using instations. <u>Calculations of an exceeding with producting and uraged waters</u>, and to save this conflict. <u>Calculations of an exceeding with producting and uraged waters</u>, and to save this conflict. This option waters this conflict generation of an exceeding water of the same state of the same stat	to agr, here and
The Zeard marcharenerbogie Gener Dage deter protek same basis plastice deter for als allog integration and accuracy performance sampling of a tractarenerbig and protect the set of the set	to agr, here and
 Initial droves well not not to go is all a bit o fit not in 2 heat or goldy counts and balls of the fit needs of grants of the second se	240
(1) ACS - relation Take 13), where "people lastic 19413" reliant Take 13, and peaking of equality o	
By the spinety along regime when give take or any and give a data or any is non-off-alling. Unless the spinety can be product when the water access and being much careful as provide when exactly and building plantane can be achieved to say and a solution. The spinet and the spinet spinet spinet and the spinet and the spinet spinet and the spinet spine spinet spine spine	The second
Selfy to car the car of specific exploring shaps deep factor exprises (Fig.) and/ int facilities of with being and engineer prices means Fig.1 for the sound waterie mention. Unlike attention areas in Finderal S and the <u>attention</u> price water price. Second 4. Unlinear exploring formation regiments for Option 2 and 3 holds water prior. Second 30 dearthout a 2010, produce to the last median to accuse, regiments the prices means prior contrast on the antonia is dearthout. SUBJ2, produce to the last median to accuse, regiments the prices means prior contrast on the antonia is dearthout. SUBJ2, produce to the last median to accuse, regiments the prices means prior contrast on the antonia list.	
 Uninum structual exploration explorates for Options 3 and 3 include source petion building importance level, build classification, SLSULS, proletions for load matter to structure, explorates to produce conserver, any confirmation for sentime to 	eric i
will be matched in accordance with 45NZS 42%	
 Protor common, when specified, shall be protect for the entry design and/or the completed celling inclusion. Env additional institutioner commons for segments areas or completion comparation to a natural. 	a.
 Sing daving shall compte as a minimum where celling plans mated up to show the patter and type of selenic backg selenic comptensions. Sing davings solutions for approxil shall view approxed in white the selenic approxed white the volting days of solutions. 	ati
Coordination of movement evention, with calling things and bracking. The minis constant while, which charge to the calling constant. Provide subside fring prime and all according constants, guilts blocking, and brinling of calling largest and blocking. Provide contracts register and of things where we calling block particles and blocking.	
 Ensure that all incelling serious are intelled antidy in accordance with 15NDS 425 inducing all components and serious over 1 are extended, from parity and extinguise, force with 15NDS 425. 	
 Cardina to splat body wh mouse and howing antical. Ly optimetr is attitud analysis, to maily populations or august replement due to a lack of excerts frings and august for conditions. We howing antice wold be analysis. 	99
Instang Instang Salam Sang Salam Sa	1
ISO Testing Paints - Cit Reports Sally Instalates (20110)	



- Protocol options are designed to assist tenderers
 - Submit offers based on consistent information
 - Reduce the number of tags
 - Reduce the number of on-site variations
 - Reduce on-site conflicts with other trades
 - Give a more accurate costing
 - Reduce the number of variables in the tender



Where Tender Documents do not nominate seismic allowances, a sample tender note is suggested:

A Provisional Sum of \$ xxx,xxx excl GST has been included for the installation of seismic restraints for the ceiling system including the engineering by an independent specialist seismic design engineer) supply, installation and certification to AS/NZS 2785:2000 and NZS 1170.5:2004.



Producer Statements

- PS 1 Design
- PS 2 Design review
- PS 3 Construction
 - PS 4 Construction Review



Roles & Responsibilities

NZS 4219

<u>Services covered under this standard must be</u> <u>designed and constructed for compatibility.</u>

Who is responsible?



- The Designer
 - Identify the Seismic Grade of the ceiling
 - Design the ceiling
 - Design appropriate seismic restraints
 - Issue a PS1 to certify the design (when required)
 - Commission a PS2 if required
 - Issue a PS4 if requested to do so



- The Tenderer
 - Ensure all ceiling details work
 - Identify the Seismic Grade of the ceiling
 - Identify a provisional sum allowance for seismic restraints (as applicable)
 - Review coordination with other trades



- The Installer
 - Prepare shop drawings (if required)
 - Submit shop drawings
 - Obtain approvals
 - Install the ceiling in accordance with the approved shop drawings or seismic specialist design
 - Inspect seismic restraints for conformance with approved design
 - Issue a PS3 on completion



- The Building Consent Authority
 - Review consent documents for Building Code compliance, especially the requirement for and design of seismic restraints
 - Review installation for conformance with consented drawings



Here is the Draft Code of Practice for Design, Installation and Seismic Restraint of Suspended Ceiling

Please download from <u>www.awcinz.org.nz</u>

We want your comments



Where to from here?

Public discussion forums Oct / Nov in

- Wellington
- Auckland
- Hamilton
- Christchurch
- Submissions close 27th November
- Launch by Minister Feb 2015
- Develop Tool Box version 2015
- Education seminars 2015





Questions Please?